

# monitor LIFTS



With gentle non-marking tracks, the ML 810 is just as at home indoors as outdoors!



The heavy-duty construction of the ML 810 and its true all-terrain capability makes it the ideal machine for rough and tough sites.



At only 1.2m wide and only 1.98m high, doorway access is easily achieved.



Weighing in at only 2.2 tonnes, the ML 810 can be very easily transported behind most tradesman's vehicles. A trailer package weighs approx. 2.75 t.

**SPECIFICATIONS**

Max working height	8.10 m
Max platform height	6.10 m
Max horizontal working outreach	3.00 m
Lift capacity / SWL	200 kg (2 persons)
Basket rotation	2 x 110°
Platform width	0.90 m
Platform length	0.80 m
Length - stowed	2.47 m
Trackbase	1.20 m
Width	1.20 m
Height - stowed	1.98 m
Turning radius	zero
Gradeability	30%
Maximum slope for elevation	5°
Drive speed - stowed (two speed)	1.8 km/h
Drive speed - raised	0.8 km/h
Weight	2200 kg
Max. ground bearing pressure	50 kN/m <sup>2</sup>
Standard features	575Ah centralized 24 volt battery filling system

Complies with AS1418.10

(E & OE)



The spacious steel basket allows for two operators to work both indoors and outdoors and can safely elevate on slopes of up to 5°!



The compact dimensions and heavy-duty design makes the ML 810 the ideal machine for tough sites such as inside tunnels.

