

BOXER®

A MORBARK® COMPANY

MADE FOR **MORE** TO KEEP PACE WITH **YOU**

385D MINI SKID STEER

As part of the 300 Series, the gas-powered **385D Mini Skid Steer** offers the power that Boxer has become known for in a smaller package, allowing you to reduce overhead and increase jobsite productivity. Designed to handle a full complement of attachments, the 385D helps minimize hand labor. Because of its reduced size and ease of operation, the 385D is ideal for the rental industry. This compact machine provides the strength to perform a variety of tasks and the versatility to get into tight area.

FEATURES AND BENEFITS

- 24.8-HP (18.49 kW) Kubota D902 Diesel Engine
- 1,100 lb (493 kg) tip capacity
- 385lb (174.6 kg) operation capacity (35% tip load)
- 35" (889 mm) wide to fit through a standard gate
- Two-pump, 2,800 psi (193 bar) hydraulic operating system develops optimum hydraulic flow to run the machine's auxiliary and propulsion systems, providing enough power to handle full-size attachments
- Dedicated oil cooler to better manage hydraulic heat generation
- Stand-on platform for operator safety and comfort
- 2-button pressure relief block
- 2.5" (64 mm) bore-welded tilt cylinder and 3" (76 mm) bore-welded lift cylinder
- 0.25" (6 mm) thick laser-cut base sides and 0.75" (19 mm) thick boom arms
- Well-balanced and stable, with excellent ground speed
- Universal compact utility loader mounting plate and quick-attach system to quickly and easily switch between any standard attachment



SPECIFICATION	US	METRIC
Engine Type		Kubota
Cooling System		Air-Cooled
HP/kW	24.8 HP	18.49 kW
Fuel Type		Diesel
Fuel Capacity	4.5 Gallons	17.1 Litres
Hydraulic Capacity	16 Gallons	60.6 Litres
System Flow (Total)	11 GPM	41.6 L/min
Hydraulic Flow (Aux)	8.0 GPM	30.3 L/min
Hydraulic Flow (Drive)	3.0 GPM	11.4 L/min
System Pressure	2800 PSI	19305.3 kPa
Engine Warranty		3 years
Product Warranty		1 year
Track Gauge	27.5"	699 mm
Track Width	7"	180 mm
Weight (No Attachment)	1913 lb	867.72 kg
Length (No Attachment)	68"	1727 mm
Length (w/Bucket)	93"	2362 mm
Width (Overall)	35"	889 mm
Height (Boom Lowered)	48"	1219.2 mm
Height (Boom Raised)	92"	2337 mm
Hinge Pin Height	70"	1778 mm
Dump Height	54"	1372 mm
Dump Angle		34 Degrees
Reach	28"	711 mm
Tip Capacity	1,100 lb	498.9 kg
Operating Capacity, 35% of tip load	385 lb	174.6 kg
Ground Clearance	5"	127 mm
Ground Speed	3.4 MPH	5.5 km/h
Ground Pressure	3.8 PSI	26.2 kPa

Updated 2/8/23