



MORBARK

MADE FOR **MORE** TO KEEP PACE WITH **YOU**



**EGER
BEEVER**

2230 BRUSH CHIPPER

The **Eger Beaver 2230 Brush Chipper** is available in trailer, track, and knuckleboom loader configurations - making it the most versatile platform across Morbark's Tree Care product line-up. Equipped with a powerful infeed system capable of whole tree chipping, the bearing-style pivot assembly provides unsurpassed material crushing power, large diameter chipping drum to power through material and high horsepower engine to get the job done faster - the Eger Beaver 2230 Brush Chipper is the perfect combination of versatility and capability.

FEATURES AND BENEFITS

- Highly configurable platform with choice of trailer, track, or knuckleboom loader configuration
- Extra wide feed wheels make feeding simple, especially when feeding with an auxiliary loader unit
- Powerful TorqMax™ top feed wheel drive system amplifies material pulling power for the most demanding applications
- Direct drive bottom feed wheel with clean-out door is speed matched to the top feed wheel to provide continuous material flow
- Large diameter chipping drum with staggered knife pockets maintains chipping power while providing consistent chip quality



MORBARKDEALERS.COM



MORBARK



EGER BEEVER

2230 BRUSH CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 4/17/2023

GENERAL	US	METRIC
Height	10'2"	3.1 m
Width	8'6"	2.59 m
Length	21'5"	6.53 m
Gross weight (approximate)	17,300 lb	7,847 kg
Suspension	(2) 10,000 lb Torflex	(2) 4,536 kg Torflex
Infeed opening (height x width)	39" x 65"	99.1 x 165.1 cm
Throat opening (height x width)	22" x 30"	55.9 x 76.2 cm
Drum (width x diameter)	29.1" x 37.4"	74 x 94.9 cm
Engine	CAT	
Horsepower	415 HP	309.5 kW
Fuel capacity	65 gallons	246 L
Hydraulic capacity	45 gallons	170.3 L
Frame	8" x 2" Tube Steel	20.3 x 5.1 cm Tube Steel
Tires	(4) 235/75Rx17.5	
Hitch	3" Pintle	7.6 cm Pintle

EQUIPMENT HIGHLIGHTS

- Dual horizontal feed wheels with TorqMax™ top feed wheel compression system, hydraulic lift assist, Variable Force™ constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and sprocket driven bottom feed wheel
- 360° height-adjustable, hydraulic swivel discharge chute with chip deflectors
- Serrated teeth and knife bars on top and bottom feed wheels
- Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
- Discharge clean-out door on bottom
- Hydraulic front stabilizer

OPTIONS INCLUDE

- Variable Speed Flow Control
- Turnbuckle for Discharge Height Adjustment
- Winch Package
- Wireless 15-function, 900Mhz Remote Control with tethered back-up system and electric over hydraulic actuator for control bar
- Dual Rear Hydraulic Stabilizers
- Axle Options Available

